

# GSM3825EAF

## 30V P-Channel Enhancement Mode MOSFET

### Product Description

GSM3825EX5F, P-Channel enhancement mode MOSFET, uses Advanced Trench Technology to provide excellent  $R_{DS(ON)}$ , low gate charge.

These devices are particularly suited for low voltage power management, such as smart phone and notebook computer, and low in-line power loss are needed in commercial industrial surface mount applications.


### Features

- -30V/-0.19A,  $R_{DS(ON)}=2500m\Omega@V_{GS}=-4.5V$   
 $R_{DS(ON)}=2900m\Omega@V_{GS}=-2.5V$   
 $R_{DS(ON)}=5000m\Omega@V_{GS}=-1.8V$
- Low-Voltage Operation
- High-Speed Circuits
- ESD Protection
- SOT-723 package design


### Applications

- Drivers : Relays, Solenoids, Lamps, Hammers
- Battery Operated Systems
- Power Supply Converter Circuits
- Load/Power Switching Smart Phones, Pagers

### Packages & Pin Assignments




## Ordering Information



Part Number	Package	Quantity Reel
GSM3825EAF	SOT-723	8000 PCS

## Marking Information



## Absolute Maximum Ratings

(T<sub>A</sub>=25°C unless otherwise noted)

Symbol	Parameter		Typical	Unit
V <sub>DSS</sub>	Drain-Source Voltage		-30	V
V <sub>GSS</sub>	Gate-Source Voltage		±10	V
I <sub>D</sub>	Continuous Drain Current(T <sub>J</sub> =150°C)	T <sub>A</sub> =25°C	-0.19	A
		T <sub>A</sub> =70°C	-0.15	
I <sub>DM</sub>	Pulsed Drain Current		-0.7	A
P <sub>D</sub>	Power Dissipation	T <sub>A</sub> =25°C	0.15	W
		T <sub>A</sub> =70°C	0.1	
R <sub>θJA</sub>	Thermal Resistance Junction to ambient		833	°C/W
T <sub>J</sub>	Operating Junction Temperature Range		-55 to +150	°C
T <sub>STG</sub>	Storage Temperature Range		-55 to +150	°C

Note1. Device mounted on FR-4 substrate PC board, 2oz copper, with minimum recommended pad layout.

## Electrical Characteristics

(T<sub>A</sub>=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static						
V <sub>(BR)DSS</sub>	Drain-Source Breakdown Voltage	V <sub>GS</sub> =0V, I <sub>D</sub> =-250uA	-30			V
V <sub>GS(th)</sub>	Gate Threshold Voltage	V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =-250uA	-0.4		-1.0	
I <sub>GSS</sub>	Gate Leakage Current	V <sub>DS</sub> =0V, V <sub>GS</sub> =±8V			±10	uA
I <sub>DSS</sub>	Zero Gate Voltage Drain Current	V <sub>DS</sub> =-24V, V <sub>GS</sub> =0V			-1	uA
R <sub>DS(on)</sub>	Drain-Source On-Resistance	V <sub>GS</sub> =-4.5V, I <sub>D</sub> =-0.5A		1.5	2.5	Ω
		V <sub>GS</sub> =-2.5V, I <sub>D</sub> =-0.2A		1.9	2.9	
		V <sub>GS</sub> =-1.8V, I <sub>D</sub> =-0.1A		2.4	5.0	
g <sub>FS</sub>	Forward Transconductance	V <sub>DS</sub> =-10V, I <sub>D</sub> =-0.25A		600		mS
V <sub>SD</sub>	Diode Forward Voltage	I <sub>S</sub> =-0.5A, V <sub>GS</sub> =0V			1.3	V
Dynamic						
Q <sub>g</sub>	Total Gate Charge	V <sub>DS</sub> =-15V, V <sub>GS</sub> =-4.5V, I <sub>D</sub> =-1A		1.0		nC
Q <sub>gs</sub>	Gate-Source Charge	V <sub>DS</sub> =-15V, V <sub>GS</sub> =-8V, I <sub>D</sub> =-1A		0.2		
Q <sub>gd</sub>	Gate-Drain Charge			0.1		
C <sub>iss</sub>	Input Capacitance	V <sub>DS</sub> =-15V, V <sub>GS</sub> =0V f=1MHz		54		pF
C <sub>oss</sub>	Output Capacitance			10.9		
C <sub>rss</sub>	Reverse Transfer Capacitance			5.8		
t <sub>d(on)</sub>	Turn-On Time	V <sub>DD</sub> =-10V, R <sub>L</sub> =47Ω, I <sub>D</sub> ≡-0.2A V <sub>GEN</sub> =-4.5V, R <sub>G</sub> =10Ω		3.8		ns
t <sub>r</sub>				11		
t <sub>d(off)</sub>	Turn-Off Time			45		
t <sub>f</sub>				20		

## Typical Performance Characteristics




Fig. 1 Typical Output Characteristics




Fig. 2 Typical Transfer Characteristics




Fig. 3 Typical On-Resistance vs.  $I_D$  and  $V_{GS}$




Fig. 4 Typical Drain-Source On-Resistance vs.  $I_D$  and  $T_J$




Fig. 5 On-Resistance Variation with  $T_J$




Fig. 6 On-Resistance Variation with  $T_J$

## Typical Performance Characteristics (continue)




Fig. 7 Gate Threshold Variation vs.  $T_A$




Fig. 8 Diode Forward Voltage vs. Current




Fig. 9 Typical Capacitance




Fig. 10 Gate Charge





Fig. 11 Transient Thermal Response

## Package Dimension

### SOT-723



DIMENSION D DOES NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. MOLD FLASH, PROTRUSIONS OR GATE BURRS SHALL NOT EXCEED 0.25mm PER INTERLEAD FLASH OR PROTRUSION SHALL NOT EXCEED 0.25mm PER SIDE.

Dimensions				
Symbol	Millimeters		Inches	
	Min	Max	Min	Max
A	0.45	0.55	0.018	0.022
A1	0.00	0.10	0.000	0.004
A2	0.45	0.55	0.018	0.022
b	0.15	0.30	0.006	0.012
b1	0.25	0.40	0.010	0.016
c	0.08	0.20	0.003	0.008
D	1.10	1.30	0.043	0.051
E	1.10	1.30	0.043	0.051
E1	0.70	0.90	0.028	0.035
e	0.4 BSC		0.016 BSC	
L	0.2	0.42	0.008	0.017





## NOTICE



- Globaltech Semiconductor assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all Globaltech Semiconductor products described or contained herein. Globaltech Semiconductor products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Globaltech Semiconductor makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

- Information furnished is believed to be accurate and reliable. However Globaltech Semiconductor assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Globaltech Semiconductor. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information without express written approval of Globaltech Semiconductor.

## CONTACT US

GS Headquarter	
	4F.,No.43-1,Lane11,Sec.6,Minquan E.Rd Neihsu District Taipei City 114, Taiwan (R.O.C)
	886-2-2657-9980
	886-2-2657-3630
	sales_twn@gs-power.com

RD Division	
	824 Bolton Drive Milpitas. CA. 95035
	1-408-457-0587